



Thermoplastfertigung

Lfd-Nr.	Masch.- Fabrikat	Masch.-Typ	Lichter Säulen- abstand	Werkzeug Einbauhöhe [mm]		max. Zuhaltekraft kN	Schnecken- durchmesser	max. Spritz- druck kN	max. Schuss- gewicht g (PF / PS)
				min.	max.				
1	Arburg	220 S	220 x 220	150	425	250	22	2320	25
2	Arburg	220 S	220 x 220	150	425	250	18	2500	17
3	Arburg	270 S	270 x 270	200	550	400	18	2500	21
4	Arburg	270 S	270 x 270	200	550	400	22	2000	31
5	Arburg	370 E	370 x 370	200	400	600	25	2500	54
6	Arburg	370 S	370 x 370	200	600	700	30	2500	97
7	Arburg	270 S	270 x 270	200	530	400	22	2500	17
8	Arburg	270 S	270 x 270	300	650	400	22	2500	25 / 31
9	Arburg	320 K	320 x 320	200	430	700	30	2470	89
10	Arburg	320 K	320 x 320	200	430	700	30	2470	89
11	Arburg	320 K	320 x 320	200	430	700	30	2470	89
12	Arburg	420 C	420 x 420	250	500	1000	35	2000	132
13	Arburg	470 S	470 x 470	350	850	1100	35	2500	129
14	Ferromatik	K 155 S	500 x 500	300	950	1550	45	1936	216
15	Ferromatik	EE 155	520 x 520	200	590	1550	40	1985	195
16	Ferromatik	K 200	560 x 560	300	1050	2000	50	2268	451
17	Ferromatik	K 200	560 x 560	300	1050	2000	60	1575	649
18	Ferromatik	K 275 S	630 x 630	300	1200	2750	60	1575	540
19	Ferromatik	EE 180	630 x 630	300	790	1800	45	1970	289
20	Ferromatik	EE 300	750 x 750	250	740	3000	60	1942	720
21	Battenfaled	HM 300	730 x 630	375	1175	3000	55	2041	540
22	Battenfeld	HM 500	1000 x 800	450	1150	5000	65	2500	1100
23	Netstal	HP4000	675 x 675	295	850	4000	40	2219	210
24	Netstal	HP4000	675 x 675	295	850	4000	40	2219	210
25	Battenfeld	EP 110	470 x 420	400	650	1100	40	2678	297
26	Battenfeld	EP 110	470 x 420	400	650	1100	40	2678	297
27	Battenfeld	EP 110	470 x 420	400	650	1100	35	3000	196,5
28	Battenfeld	EP 110	470 x 420	400	650	1100	35	3000	196,5
29	Battenfeld	EP 180	570 x 520	425	750	1800	40	2678	257,5

